



The best way to lubricate your coupling-gaskets is by using Profit lubricant. Super Glidex is high quality silicon-oil based lubricant, specially formulated to enable an easy and fast application.

## Applications

- Designed to prevent pinching of rubber self-sealing gaskets in couplings combined to connect grooved pipes, PROFIT fittings and PROFIT valves.
- Can also be used for assembly of plastic pipes with O-ring gaskets.
- Application temperature range : -30 ° up to + 45 °C
- Can be applied on EPDM and NBR rubber gaskets.
- Guidance:
  - Ensure that the pipe and the coupling gasket are free of dust, dirt and debris prior to application.
  - Apply by means of a brush, sponge or swab. We advise to always use Profit safety gloves.
  - Apply the lubricant on inside and outside of the gasket and/ or on the outside of the tubes in the groove-area.
  - Note: this lubricant is available in two versions:
    1. 175g Tube including a sponge-applicator.
    2. 1000g Container.



## Technical properties

- Colour: snow-white.
- Consistency: creamy.
- pH-value : 6.5- 7.
- Water -soluble.
- Bio-degradable.

## Storage

- Recommended storage temperature range : 0 °C to + 30 °C
- Keep separate from foods, fertilisers and/or other sensitive materials.
- Keep containers shut and out of direct sunlight, when not in use.
- Respect the expiry date. The product life is minimum 2 years after production date.

## Safety information

- Page 2 + We refer to our separate document 'Safety Data Sheet', available on request.



## First Aid Measures

	Description
General information	In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
Inhalation	Bring the person into fresh air and stay with him.
Skin contact	Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.
Eye contact	Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
Ingestion	Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.
Burns	Not applicable.

## Firefighting Measures

	Description
Extinguishing media	Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.
Special hazards arising from the substance or mixture	If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
Advice for firefighters	No specific requirements.

## Accidental release measures

	Description
Personal precautions, protective equipment and emergency procedures	No specific requirements.
Environmental precautions	No specific requirements.
Methods and material for containment and cleanup	Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.
Reference to other sections	See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.